

Harness the
power of

Braemar
By SEELEY INTERNATIONAL 

Multi-split
system

100%
Australian
owned!

Multiple
room
solutions

Scan
to view
product
brochure



Multi-split system air conditioning enables you to cool or heat multiple rooms individually (up to five) from just one outdoor unit. Save running costs by heating or cooling rooms as required with different temperature settings in each room. Choose from the high wall split¹, bulkhead or cassette indoor unit range to suit your indoor space requirements.



Low running costs

Inverter technology and high energy efficiency results in significant savings.



Black fin

The highest-rated and most corrosion resistant protective coating, enhancing longevity against the harsh Australian elements.



Quiet operation

Inside and outside the home.



Wider operating temperatures

Suitable for any climate.



R32 Refrigerant

68% lower Global Warming Potential and more energy efficient than R410A.



Warranty

Quality that lasts.
5 year comprehensive warranty.



Quality

80 year history of Braemar excellence and reliability!



DRED

Demand response enabled device capability is standard.



Bulkhead



High wall split



Cassette



For more information visit seeleyinternational.com

Braemar multi-split system air conditioning¹

Bulkhead indoor units

Cassette indoor units

Model		Indoor	NDHV25D1S	NDHV35D1S	NDHV50D1S	NDHV70D1S	NBHV25D8S	NBHV35D8S	NBHV50D8S	NBHV71D8S	
Cooling Capacity		kW	2.65	3.5	5.0	7.0	2.8	3.5	5.0	7.1	
Sensible Cooling Capacity		kW	2.0	2.54	3.77	5.29	1.84	2.54	3.77	5.39	
Heating Capacity		kW	2.8	4.0	5.5	8.0	2.8	4.0	5.5	7.8	
Dehumidifying Volume		l/hr	0.8	1.4	1.8	2.5	1.4		1.8	2.5	
Indoor Unit	Power Supply	V / Hz / Ph	230 / 50 / 1				230 / 50 / 1				
	Airflow (Min ~ Max)	l/s	105 ~ 180	144 ~ 194	203 ~ 244	250 ~ 417	206 ~ 330		206 ~ 383	412 ~ 565	
	ESP Nominal (Min ~ Max)	Pa	25 (0 ~ 60)				25 (0 ~ 125)				
	Sound Pressure Level (Min ~ Max)	dB(A)	32 ~ 39	34 ~ 41		36 ~ 45		28 ~ 41		28 ~ 43	37 ~ 46
	Outline Dimension (WxDxH)	mm	710x450x200		1010x450x200		900x655x260		570x570x265		840x840x200
	Net Weight	kg	18.5	19.0	25.0	31.0	17		21		
Facia Panel	Model	No.	N/A				TF05		TF06		
	Outline Dimension (WxDxH)	mm	N/A				670x670x47.5		950x950x52		
	Net Weight	kg	N/A				3.0		6.0		
Supply Air Outlet	Height	mm	122			215		N/A			
	Width	mm	585		885		741		N/A		
Return Air Inlet	Height	mm	200			234		N/A			
	Width	mm	710		1010		871		N/A		
Pipe	Outer Diameter	Liquid Pipe	mm (Inch)	Ø6.35 (1/4)				Ø6.35 (1/4)			
		Gas Pipe	mm (Inch)	Ø9.52 (3/8)		Ø12.7 (1/2)		Ø15.88 (5/8)		Ø9.52 (3/8)	

Multi-split outdoor units

Model		Outdoor	NCHV05D12B	NCHV07D13B	NCHV08D14B	NCHV10D14B	NCHV12D15B		
Cooling Capacity		kW	5.3	7.3	8.2	10.6	12.3		
Cooling Capacity Range (Min ~ Max)		kW	2.14 ~ 5.8	2.3 ~ 9.2	2.3 ~ 11.0	2.6 ~ 12.0	2.6 - 15.2		
Heating Capacity		kW	5.6	8.3	8.8	11.4	12.6		
Heating Capacity Range (Min ~ Max)		kW	2.58 ~ 6.5	2.8 ~ 9.2	2.8 ~ 10.25	3.0 ~ 14.0	3.0 - 15.5		
Max Indoor Capacity		kW	7.9	10.9	12.3	15.1	18.4		
AEER		W/W	3.78	3.67	4.28	3.95	3.92		
ACOP		W/W	4.24	4.09	4.09	3.95	3.89		
Electrical Data	Power Supply		V / Hz / Ph	230 / 50 / 1					
	Power Input (Nominal)	Cooling	kW	1.38	1.96	1.88	2.65	3.10	
		Heating	kW	1.30	2.00	2.12	2.85	3.20	
	Maximum Current Input		A	11.0	15.0	16.0	21.7		
Minimum Circuit Breaker Outdoor		A	16	20		25			
Outdoor Unit	Maximum Drive IDU		No.	2	3	4		5	
	Sound Pressure Level		dB(A)	54	58		60		
	Outline Dimension (W x D x H)		mm	822 x 352 x 550	964 x 402 x 660		1020 x 427 x 826		
	Net Weight		kg	34.0	47.5	51.0	72.0	73.0	
Refrigerant R32	Chargeless Length		m	40				50	
	Additional Charge		g/m	20					
Pipe	Outer Diameter	Liquid Pipe	mm (Inch)	2 x Ø6.35 (1/4)	3 x Ø6.35 (1/4)	4 x Ø6.35 (1/4)		5 x Ø6.35 (1/4)	
		Gas Pipe	mm (Inch)	2 x Ø9.52 (3/8)	3 x Ø9.52 (3/8)	4 x Ø9.52 (3/8)		5 x Ø9.52 (3/8)	
	Maximum Distance	Height	m	15				25	
		Length	m	30					
		Sum of all Indoors	m	50	60	70	80	100	
Ambient Temperature Operating Range		Cooling	°C	-15 ~ 52					
		Heating	°C	-22 ~ 24					

1. See Austral-air® flyer or full brochure for high wall split indoor unit technical specifications.
Information in this flyer was correct at the time of preparation.
Cat No M487 REV B DEALER (0825)

Notes: